SmartACU2000

Front

Back

SmartACU2000 (Smart Array Controller Unit) is a powerful integration of PV array communication and other smart functions.

Smart

- SmartLogger2000 built-in
- Anti-PID module built-in (optional)
- Multiple communication interfaces including PLC, RS485, Fast Ethernet, and SFP ports, flexible applications

Simple

- Integrated communication unit with multiple functions built-in
- Easy installation with SmartLogger2000 & anti-PID module pre-assembled inside the cabinet

Reliable

- Industrial application and carrier-class reliability

Description	Specification
	Configuration
SmartLogger	SmartLogger2000
PLC	Optional
Anti-PID	Optional
	Environment
Operating Temperature	-40℃ ~ +60℃ (-40 °F ~ +140 °F)
Storage Temperature	-40℃ ~ +85℃ (-40 °F ~ +185 °F)
Relative Humidity (Non-Condensing)	5% ~ 95%
Operating Altitude	0 ~ 4,000m (0 ~ 13,123 ft.)
	Mechanical
Cabling	Bottom in & out
Maintenance	Front & Back
Dimensions (W/H/D)	600mm × 1,100mm × 600mm (2 × 3.6 × 2 ft.)
Weight	65 kg (143.3 lb.)
Protection Rating	IP65
Installation Option	Ground Mounting, Wall Mounting, Rail Mounting

info.energyeu@huawei.com
inverter@huawei.com
Tel.: 49 911 255 22 3053
Tel.: 800 0889977

www.huawei.com/solar

sales@photomate.eu
www.photomate.eu